



圖 1 雙橡膠圈鋼襯管接頭詳圖




表 2 雙橡膠圈鋼襯管接頭尺度

單位：mm

標稱管徑	內徑 D	管壁厚度 (¹)tc	鋼襯厚度 (²)ty	鋼襯外徑 F	承口深度 C	插口長度 E	橡膠圈直徑 d	接頭內寬 隙 J	接頭外寬 隙 K	有效長度 L	接頭外環 (°)	
											W	tr
700	700	88	最小厚度 1.5	760.2	145	150	20	20	25	2500 5000 6000	150	10
800	800	100		860.2								
900	900	105		960.2								
1000	1000	110		1076.2								
1100	1100	116		1176.2								
1200	1200	125		1276.2								
1350	1350	138		1439.2								
1500	1500	150		1589.2								
1650	1650	162		1745.2								
1800	1800	175		1895.2								
2000	2000	210		2101.2								
2200	2200	215		2301.2								
2400	2400	225		2501.2								
2600	2600	242		2701.2								
2800	2800	258		2901.2								
3000	3000	275		3101.2								
3200	3200	282	3333.0									
3400	3400	300	3533.0									
3600	3600	316	3733.0									
3800	3800	332	3933.0									
4000	4000	348	4133.0									